

Job Name: 26-1216 Hayden Rd. Sanitary Job Location: Owensboro, KY Contractor: Winwater Hartford KY Co.					Plant: Beaver Dam 7/7/2026 2:19:15 PM		Tech: S. Felletter PC: A. Chambers									
Structure ID: A1 SS-MH																
P1 MH048DHVFCDARED			MH DH RISER Custom Ht, w/ConBlock-CDA Red T/F													
P4) 24" - CASTING HEIGHT - 7" P3) 48" - ECC CONE w/ 24" HOLE, w/ConBlock-CDA Red F/G - 30" P2) 48" - MH RISER w/ConBlock-CDA Red T/G - 36" P1) 48" - MH DH RISER Custom Ht, w/ConBlock-CDA Red T/F - 43" 1) JOINT WRAP - 0.065"x6"x50' CONSEAL CS212 1) JOINT WRAP PRIMER - CONSEAL CS-75 (1 gal.) 1) CASTING - HOE MC-315 F/C Sanitary 2) 48" - Conseal CS-102 1.00" (Double) 1) 24" - Conseal CS-102 1.00" (Double) 2) DOGHOUSE - 12"x16" 1) PSX - 12-08 NYLO 9) MH Step ML-10-TDS-NCR - 10"						0 lb 1961 lb 2515 lb 2811 lb 0 lb 0 lb 258 lb 0 lb 0 lb 0 lb 8 lb 0 lb ----- 7553 lb		Structure Notes: 1. PER ASTM C478 SPECIFICATIONS. 2. CONCRETE = 4,000 PSI AT 28 DAYS. 3. ADMIXTURE = CONBLOCK CDA RED. 4. CASTING BY ICAST (HOE MC-315 F/C "SANITARY"). REINFORCING PER ASTM A615 (GRADE 60). - CONE (As .12) - RISER/WALLS (As .12)								
Rim: 429.38' Rim to Invert: 9.36' Slack: 0.32" Sump: 4" Step Position: 270°																
Position	Elev	Angle	Ext. (cw)	Pipe	Pipe OD	Connector	Hole	Horz Size	Up ()	Offset						
Invert 1	420.02'	0°	0"	8" PVC SDR26	8.5"	DOGHOUSE 12"x16"	12" x 16"	12.129"	0"	0"						
Invert 2	420.12'	90°	45.553"	8" PVC SDR26	8.5"	PSX 12-08 NYLO	12"	12.129"	3.2"	0"						
Invert 3	420.02'	180°	91.106"	8" PVC SDR26	8.5"	DOGHOUSE 12"x16"	12" x 16"	12.129"	0"	0"						
Invert 4																
Invert 5																
Invert 6																
Invert 7																
Invert 8																
(P4) (P3) (P2) (P1) << RIGHT-SIDE UP VIEW (int. dimensions) Invert: 3 Degree: 180° Horz: 75.398" Hole: 12" x 16" Up(): 0" Invert: 2 Degree: 90° Horz: 37.699" Hole: 12" Up(): 3.2" Invert: 1 Degree: 0° Horz: 0" Hole: 12" x 16" Up(): 0" Step: 270° Horz: 113.097" + 0° - UPSIDE-DOWN VIEW (int. dimenions) INSIDE WALL DIMENSIONS 0° 90° 180° 270° 360° EXT 43" (P1) 0" 37.699" 75.398" 1 2 3 0" 3.2" 0" <table><tr><td>Coating (Int): Coating (Ext):</td><td>Seam Up: Tongue Seam Dn: Flat</td><td>Wall Thickness: 5" Floor Height: 0"</td><td>Height (Int): 43" Height (Ext): 43"</td><td>Weight (Net): 2811 lb Volume (Net): 0.72cu.yd</td></tr></table>												Coating (Int): Coating (Ext):	Seam Up: Tongue Seam Dn: Flat	Wall Thickness: 5" Floor Height: 0"	Height (Int): 43" Height (Ext): 43"	Weight (Net): 2811 lb Volume (Net): 0.72cu.yd
Coating (Int): Coating (Ext):	Seam Up: Tongue Seam Dn: Flat	Wall Thickness: 5" Floor Height: 0"	Height (Int): 43" Height (Ext): 43"	Weight (Net): 2811 lb Volume (Net): 0.72cu.yd												