


NOTES:

1. MANUFACTURED TO ASTM C-478 (LATEST REVISION).
2. CONCRETE = 4,000 PSI AT 28 DAYS.
3. REINFORCING PER ASTM A615 (GRADE 60).

PRODUCTION WORK ORDER		PRODUCT I.D.: GR36x6x4	DESCRIPTION: GRADE RING 36" DIA x 4" HT.
	QUALITY CONTROL CHECKLIST	PRODUCT VIEW: RIGHT SIDE UP	CUSTOMER: State Group
	<input type="checkbox"/> ALL DIMENSIONS CORRECT.	PLANT: BEAVER DAM, KY.	PROJECT: KYMEA
	<input type="checkbox"/> WIRE LOOP ANCHORS INSTALLED.	WEIGHT: 266 LBS.	STRUCTURE ID.: GR
	<input type="checkbox"/> HOLE LOCATION CORRECT.	TOP JOINT: FLAT	QUOTE/SALES ORDER NO: 25-2219P2
	<input type="checkbox"/> REINFORCING CORRECT.	BOTTOM JOINT: FLAT	PC: J.H. ROSS, PE
	<input type="checkbox"/> FINISH ON SLAB SURFACE UNIFORM.	QC CHECK INITIALS:	DRAWING: J. HORSLEY
	<input type="checkbox"/> OUTSIDE TOP EDGE ROUNDED.		DATE: 02/13/26
<input type="checkbox"/> JOINT INSTALLED IF NEEDED.		SCALE: NTS	
			PG. 1 of 1