

Contractor: Louisville Paving and Construction

PC:	J. Jarvis
TECH:	J. Horsley - A
Plant:	100




Slack: 0"

1. PER MSD CATCH BASIN TYPE 1 / ASTM C-913 SPECS
2. CONCRETE: 4,000 PSI AT 28 DAYS
3. REINFORCEMENT: #5 BAR @ 12" C.C. E.W. (GRADE 60)
4. HOE 595 FRAME & GRATES SUPPLIED BY OTHERS

P2) 36" x 36" - CASTING HEIGHT - 3"
P1) 36" x 36" - BOX BASE 8inW, 8inF F/n - 30"
1) 36" x 36" - Conseal CS-102 1.00"
2) Hole - 24

0 lb
4752 lb
0 lb
0 lb


Structure Total: 4752 lb



Position	Elev	Angle	Pipe	Pipe OD	Hole	Connector	Up (↓)	Ref
Rim	563.94'							
Reducer								
Invert 1	561.19'	90°	18" HDPE	21.2"	24"	Hole 24	-3"	P1
Invert 2	561.19'	270°	18" HDPE	21.2"	24"	Hole 24	-3"	P1
Invert 3								
Invert 4								
Invert 5								
Invert 6								
Invert 7								
Invert 8								

36" x 36" - CASTING HEIGHT - 3" - (P2)

36" x 36" - BOX BASE 8inW, 8inF F/n - 30" - (P1)



Submittal Drawing
6/17/2026 5:40:17 PM

SUBMITTAL
APPROVED BY: