




Structure ID: ICAST LI3 (2)

P1 HWPP414TY3


4" - HW Perforated Pipe Type 3 (4 to1) F/F

PIPE DIA.	SLOPE	DIMENSIONS				CLASS "A" CONCRETE
		L	H	A	C	
4"	2:1	3'-4 1/2"	1'-6 1/2"	1'-6"	6"	0.38
	3:1	5'-1 1/2"	1'-6 1/2"	2'-3"	9"	0.56
AND	4:1	6'-9 3/4"	1'-6 1/2"	3'-0"	1'-0"	0.74
6"	5:1	7'-2 1/2"	1'-6 1/2"	1'-5"	1'-5"	0.62
8"	2:1	3'-2 1/2"	1'-6"	1'-6"	6"	0.43
	3:1	5'-8 1/4"	1'-10 3/4"	2'-3"	9"	0.63
10"	4:1	7'-7"	1'-4 3/4"	3'-0"	1'-0"	0.83
	6:1	8'-4 1/2"	1'-4 3/4"	1'-5"	1'-5"	0.73
12"	2:1	4'-3"	2'-4"	1'-6"	6"	0.47
	3:1	6'-3"	2'-4"	2'-3"	9"	0.69
14"	4:1	8'-4"	1'-8"	3'-0"	1'-0"	0.91
	5:1	9'-5"	1'-7"	1'-5"	1'-5"	0.83

2X2 MESH, 16 GAUGE
HOT DIP GALVANIZED
WITH 1" X 1" SQUARES




DETAIL "A"



2:1 (TYPE 1)
1,520 LBS.

3:1 (TYPE 2)
2,240 LBS.



4:1 (TYPE 3)
2,960 LBS.

6:1 (TYPE 4)
2,480 LBS.

NOTES:

1. CONCRETE: KYTC APPROVED.
2. REINFORCING: #4 BAR @ 12" C/C E.W. - GRADE 60, (WITH 2" CONCRETE COVER MINIMUM)
3. REINFORCING BARS TO BE TACK WELDED OR TIED.
4. PIPE AND LIFTING ANCHOR POCKETS TO BE GROUTED WITH KYTC APPROVED NON-SHRINK GROUT.
5. DRAWING TO BE USED IN CONJUNCTION WITH KYTC STD. DRAWING RDP-010-09 AND THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
6. 3/8" CHAMFER ON ALL EXPOSED EDGES.

APPROVED FOR DESIGN ONLY

Approved
Jared A. Jarvis
KYTC DISTRICT ENGINEER
REGION 3 SOUTH

DIVISION OF CONSTRUCTION



INFRASTRUCTURE PRECAST, INC.
1801 WEST 7TH ST. BOONVILLE, KY. 40309
PHONE (270) 363-3238, FAX (270) 368-7484

KYTC PERFORATED PIPE HEADWALLS

DRAWING NO. KYTC P1-HW
DATE 12-07-21
DESIGNED BY J. J. JARVIS, P.E.
CHECKED BY J. J. JARVIS, P.E.
WEB: WWW.ICASTINC.COM