


NOTES:

1. PER ASTM C913 LATEST REVISIONS.
2. CONCRETE = 4,500 PSI AT 28 DAYS.
3. REINFORCING PER ASTM A615 (GRADE 60).
#5's AT 6" C/C EACH WAY

PRODUCTION WORK ORDER		PRODUCT I.D.: CTS	DESCRIPTION: CUSTOM TOP SLAB 61" x86.5"x 6" HT (SOLID)	
	QUALITY CONTROL CHECKLIST ALL DIMENSIONS CORRECT. LIFTERS INSTALLED. OPENING OFFSET. REINFORCING CORRECT. SHIP-LAP TONGUE INSTALLED. EDGES CHAMFERED. ANY PATCHWORK ACCEPTABLE.	PRODUCT VIEW: RIGHT SIDE UP	CUSTOMER: ALPHA ENERGY SOLUTIONS	
		PLANT: BEAVER DAM, KY.	PROJECT: LOWERY LANE TOP SLAB	
		WEIGHT: 3,738 LBS.	STRUCTURE: SOLID LID	
		TOP JOINT: FLAT	QUOTE/SALES ORDER NO: 25-3208	
		BOTTOM JOINT: FLAT	CHECK: B. SMITH	DRAWING: J. HORSLEY
QC CHECK INITIALS:	DATE: 11/06/25	SCALE: NTS	PG. 1 of 1	