


GENERAL NOTES:

1. MANUFACTURED PER ASTM C-913 SPECIFICATIONS
2. CONCRETE: 5,000 PSI AT 28 DAYS
3. REINFORCEMENT: #5 BAR @ 6" C.C. E.W. (GRADE 60) - 2" MIN. REBAR CLEARANCE (TYP)
4. WEIGHT: 17,325 LBS
5. 36" X 36" HATCH SUPPLIED BY OTHERS - TO BE CAST INTO TOP OF MONOTOP
6. ALUMINUM LADDER & SAFETY POST SUPPLIED BY OTHERS
7. LINK-SEAL CONNECTORS SUPPLIED BY OTHERS
8. LIFTERS: 4 EA. 5CA14 CONAC A-ANCHORS FOR PLANT & FIELD HANDLING
9. TOP SURFACE TO RECEIVE LIGHT BRUSH FINISH

PRODUCTION WORK ORDER		PRODUCT I.D.: BX72144-06W06T-VF-MT	DESCRIPTION: 72" X 144" X 48" MONOTOP, 6" WALLS & 6" TOP	
	QUALITY CONTROL CHECKLIST	PRODUCT VIEW: RIGHT SIDE UP	CUSTOMER: STRIEGEL DESIGN & CONSTRUCTION	
	<input type="checkbox"/> ALL DIMENSIONS CORRECT.	PLANT: BEAVER DAM, KY	PROJECT: 2025 NEW WELL FIELDS	
	<input type="checkbox"/> LIFTERS INSTALLED.	WEIGHT: 17,325 LBS	STRUCTURE: 2-54406-14	
	<input type="checkbox"/> HOLE LOCATION(S) CORRECT.	TOP SECTION JOINT: GROOVE	ORDER NO: 25-4406	
	<input type="checkbox"/> REINFORCING & SPACING CORRECT.	BASE SECTION JOINT: N / A	PE: J.H. ROSS	DRAWING: K. CARDWELL
<input type="checkbox"/> HATCH LOCATION & ORIENTATION.	QC CHECK INITIALS:	DATE: 02/11/26	SCALE: NTS	PG. 1 OF 1
<input type="checkbox"/> EDGES CHAMFERED.				
<input type="checkbox"/> JOINT INSTALLED.				

Job Number:

25-4406

Job Name:

2025 New Well Fields

Structure:

2-54406-14

Note:

36" x 36" Hatch Supplied By Others
To Be Cast Into Top of Monotop