



15" - FLARED END SECTION SPIGOT (INLET) F/F



INFRASTRUCTURE PRECAST, INC.
381 WEST 7TH ST., BEAVER DAM, KY. 42320
PHONE: (270) 363-2238, FAX: (270) 298-7424


DRAWING DATE: SEPTEMBER 2, 2022

DRAWING NAME: 15-FES-TYPE 2

SCALE: NTS

CATALOG I.D.: 15-RCP-FES

WEB ADDRESS: WWW.ICASTING.COM



GENERAL NOTES:

1. FLARED END SECTION IS MANUFACTURED AND TESTED IN ACCORDANCE WITH ASTM C-635 AND C-636.
2. PIPE JOINTS MEET ASTM C-1429 AND C-1429-1 SPECIFICATIONS.
3. INSTALL REINFORCED CONCRETE PIPE PER ASTM C-1429-STANDARD PRACTICE FOR INSTALLATION OF PRECAST CONCRETE PIPE.
4. FLARED END SECTION REINFORCING IS IN ACCORDANCE WITH ASTM C-76.
5. WEIGHT SHOWN IS CALCULATED USING 150 LBS. PER CUBIC FT. UNIT WEIGHT OF CONCRETE.

THIS DRAWING IS THE PROPERTY OF INFRASTRUCTURE PRECAST, INC. ANY USE OR DUPLICATION OF THIS DRAWING WITHOUT PRIOR AUTHORIZATION IS STRICTLY PROHIBITED.