



P4) 24" - CASTING HEIGHT - 6"	0 lb	Structure Notes: 1. JBS-1155 PROVIDED BY ICAST. 2. PER ASTM C478 SPECIFICATIONS. 3. CONCRETE = 4,000 PSI AT 28 DAYS. 4. REINFORCING PER ASTM A615 (GRADE 60). - CONE (As .12) - RISER (As .12) - FLOOR (As .31) #5 BARS AT 12" C.C.E.W.
P3) 24" - XYPEX GRADE RING - 6"	405 lb	
P2) 48" - ECC XYPEX CONE w/ 24" HOLE - 42"	3116 lb	
P1) 48" - MH BASE w/XYPEX - 36"	3797 lb	
1) JOINT WRAP PRIMER - CONSEAL CS-75 (1 gal.)	0 lb	
1) JOINT WRAP - 0.065"x12"x50' CONSEAL CS212	0 lb	
1) 48" - MH INVERT CHANNEL w/XYPEX - FULL HEIGHT	1440 lb	
1) CASTING - JBS 1155 F/C SANITARY	250 lb	
1) 48" - Conseal CS-102 1.00" (Double)	0 lb	
2) 24" - Conseal CS-102 1.00" (Double)	0 lb	
1) PSX - 12-06 NYLO	8 lb	
7) MH Step ML-10-TDS-NCR - 10"	0 lb	
Structure Total:	9016 lb	



48" - ECC XYPEX CONE w/ 24" HOLE - 42" - (P2)

Coating (Int):	Seam Up: Flat	Wall Thickness: 5"	Height (Ext): 42"	Weight (Net): 3116 lb
Coating (Ext):	Seam Dn: Groove			Volume (Net): 0.8cu.yd