

Rod Chomper Rebar Cutter & Bender

Preventive Maintenance & Lockout/Tagout (LOTO) Checklist

Machine ID:		Model:		Location:	
Inspector:		Date:		Hours:	

LOCKOUT / TAGOUT – REQUIRED BEFORE MAINTENANCE

■ Notify affected employees
■ Shut down machine
■ Disconnect power / shut down engine
■ Apply lock(s) and tag(s)
■ Relieve hydraulic pressure
■ Verify zero energy state

DAILY PRE-OP CHECK

■ Hydraulic oil level full
■ No visible hydraulic leaks
■ Guards installed and secure
■ Foot switch operational
■ Electrical cord undamaged
■ Knives, pins, wheels acceptable

WEEKLY / GREASING

■ Grease daily fittings (if applicable)
■ Grease weekly fittings
■ Pivot bolts and lock nuts tight
■ Inspect hoses and fasteners

MONTHLY / PERIODIC

■ Relief valve $\leq$ 3000 PSI
■ Lubricate foot switch pivot
■ Electrical connections acceptable

200-HOUR / ANNUAL

■ Replace hydraulic filter (200 hrs)
■ Replace hydraulic oil – AW-32 (annual)
■ Inspect blades, pins, wheels, cylinders

Comments / Corrective Actions:
